

CANOVATE A/W 200-600 CHILLER TECHNICAL SPECIFICATIONS



MODEL		A/W 200	A/W 300	A/W 400	A/W 500	A/W 600
Cooling Capacity (1) 15 °C water outlet, 25 °C ambient temprature	kcal/h	265.000	362.700	532.160	628.480	796.720
	kW	308	421	618.8	730.80	926.41
Cooling Capacity (2) 15 °C water outlet, 35 °C ambient temprature	kcal/h	228.600	315.200	460.320	560.240	692.360
	kW	265	366.5	535	651.44	805.06
Cooling Capacity (3) 7 °C water outlet, 25 °C ambient temprature	kcal/h	205.400	270.020	380.840	480.485	570.480
	kW	238	313.9	442.81	564.51	663.34
Cooling Capacity (4) 7 °C water outlet, 35 °C ambient temprature	kcal/h	172.000	252.140	340.030	430.080	524.180
	kW	200	293.18	395.38	500.09	609.39
Compressor Type		Screw	Screw	Screw	Screw	Screw
Compressor Piece		2	2	2	2	2
Compressor Absorbed Power (1)	kW	53.10	72.58	114.59	125.86	159.65
Compressor Absorbed Power (2)	kW	60.22	83.30	130.60	155.10	191.66
Compressor Absorbed Power (3)	kW	62.63	82.60	119.67	152.43	174.47
Compressor Absorbed Power (4)	kW	58.82	83.71	123.55	156.25	179.23
Refrigerant		R407C	R407C	R407C	R407C	R407C
Refrigerant Circuit		2	2	2	2	2
Fan Piece		4	6	8	8	10
Fan Power	kW	7.2	10.8	14.2	14.2	17.2
Diemsions (LxWxH)	cm	260x160x240	340x200x240	420x200x240	500x200x240	600x200x240